

1 **SYSTEMS AND METHODS FOR KNOWLEDGE DISCOVERY**

2 **IN SPATIAL DATA**

3
4 **CONTRACTUAL ORIGIN OF THE INVENTION**

5 This invention was made with United States Government support under Contract
6 No. DE-AC07-99ID13727 awarded by the United States Department of Energy. The
7 United States Government has certain rights in the invention.

8
9 **RELATED APPLICATION**

10 This application claims priority from United States provisional application S/N
11 60/174,389 filed January 3, 2000 and is incorporated by reference.

12
13 **Field of the Invention**

14 The present invention relates to systems and methods for knowledge discovery in
15 spatial data. More particularly, the present invention relates to systems and methods for
16 mining data from a spatial database and more specifically to optimizing a recipe for a spatial
17 environment by extracting knowledge from a spatial database.

18
19 **Prior State of the Art**

20 In recent years, the contemporary data mining community has developed a plethora
21 of algorithms and methods used for different tasks in knowledge discovery within large
22 databases. Few of the algorithms and methods are publicly available and a researcher who

1 wishes to compare a new algorithm with existing algorithms, or analyze real data, finds the
2 task daunting. Furthermore, as algorithms become more complex, and as hybrid algorithms
3 combining several approaches are suggested, the task of implementing such algorithms from
4 scratch becomes increasingly time consuming.

5 Current data mining techniques are unable to fully extract knowledge from high dimensional
6 data in large spatial databases, while data analysis in typical knowledge discovery software
7 is limited to non-spatial data.

8 It is also known that there is no universally best data mining algorithm across all
9 application domains. Advances in spatial databases have allowed for the collection of huge
10 amounts of data, for example, in various GIS applications. A subfield of data mining that
11 deals with the extraction of implicit knowledge and spatial relationships not explicitly stored
12 in spatial databases is called spatial data mining. However, no GIS system with significant
13 spatial data mining functionality is currently available. There has been some spatial data
14 mining software development, but most systems are primarily based on minor modifications
15 of non-spatial data mining systems.

16 In addition, different data mining algorithms for spatial data are implemented in
17 different programming environments. For example, interpreted languages like S-PLUS and
18 MATLAB are sometimes slower than algorithms implemented in C or C++. To allow end-
19 users to benefit from multiple spatial data mining approaches, there is a need for the
20 development of a system which will integrate all implemented methods in a single
21 environment and thus reduce user's efforts in planning their management actions.

1 Precision agriculture is one of the applications which will prosper from novel spatial
2 data mining techniques. Technological advances, such as global positioning systems,
3 combine-mounted on-the-go yield monitors, and computer controlled variable rate
4 application equipment, provide an opportunity for improving upon the traditional approach
5 of treating agricultural fields as homogenous data distributions. In precision agriculture,
6 environmental characteristics at a sub-field level are used to guide crop production decisions.
7 Instead of applying management actions and production inputs uniformly across entire fields,
8 they are varied to better match site-specific needs, thus increasing economic returns and
9 improving environmental stewardship. Lower costs and new sensor technologies are
10 enabling agriculture producers to collect large quantities of site-specific data from which
11 future site-specific management decisions can be derived. However, methodologies to
12 efficiently interpret the meaning of these large and multi-featured data sets are lacking.
13 Therefore, for precision agriculture and other applications, spatial data mining techniques
14 are necessary in order to successfully perform data analysis and modeling.

15 Furthermore, precision agriculture data is inherently distributed at multiple farms and
16 cannot be localized on any one machine for a variety of practical reasons including
17 physically dispersed data sets over many different geographic locations, security services and
18 competitive reasons. In such situations, it would be advantageous to have a distributed data
19 mining system that can learn from large databases located at multiple sites.

20 A system for spatial data analysis that provides flexible machine learning tools for
21 supporting an interactive knowledge discovery process is needed. Furthermore, that system
22 should be functional in a large centralized or distributed database. In addition, the system

1 should allow for rapid software development for data analysis professionals as well as
2 systematic experimentation by spatial domain experts without prior training in machine
3 learning or statistics.

4 5 **SUMMARY OF THE INVENTION**

6 The present invention overcomes the inability of the prior art to effectively mine
7 usable spatial data from spatial data sources and provides systems and methods for
8 knowledge discovery in spatial databases. In one embodiment, the data mined or extracted
9 from spatial databases can be used to optimize a recipe for use in a spatial environment. For
10 example, there are a variety of spatial environments in precision agriculture, such as
11 agricultural fields, farm equipment, combines, and the like, and each one can have an
12 associated spatial database that contains data. A spatial database for an agricultural field, for
13 example, can contain information such as type and amount of fertilizer applied, crop yield,
14 water use, slope, and the like. A spatial database for a combine can contain information such
15 as variations in combine velocity, fan speed, and the like, across the field. With regard to
16 agricultural fields, the present invention can be used to optimize a recipe for applying
17 fertilizer to the agricultural field. The systems and methods of the present invention can be
18 extended to other spatial environments and spatial data. The present invention is not limited
19 to precision agriculture, but can be expanded to spatial environments such as nuclear
20 reactors, waste dumps, environmental stewardship sites, and the like that may be described
21 by spatial databases.

1 The present invention allows users to load or generate spatial data and then
2 manipulate the spatial data as desired. The user, through a unique graphical user interface
3 applies various spatial data mining algorithms to the spatial data. One objective of the user
4 is to model and classify the spatial data according to spatial data mining algorithms. The
5 user can also create new modeling algorithms based on existing algorithms which augments
6 the ability to analyze spatial data. Yet another objective of the present invention is to allow
7 users to discover which attributes have more influence than others. All of these objectives
8 are achieved through a unique spatial data analysis and modeling module. Ultimately, the
9 results of the spatial data analysis are applied to optimize the approach to precision
10 agriculture or other industries. For example, the results would be beneficial in providing
11 site-specific recommendations for fertilizing a field on a point-by-point basis rather than
12 applying the same amounts and types of fertilizer to the whole field.

13 The spatial data is analyzed through the spatial data analysis and modeling module,
14 which includes a number of different modules, all of which may or may not be implemented
15 when analyzing a particular set of spatial data. The loading module assists the user in
16 loading or generating spatial data. The loading module also performs basic data partitioning.
17 The inspection module provides basic statistical information such as scatterplots, histograms,
18 QQ plots, and 2-D and 3-D surface plots. The inspection module also provides variograms
19 and correlograms. The preprocessing module cleans up and eliminates noise in the data. The
20 preprocessing module also allows the user to normalize and discretize the data. The user can
21 also select or extract the most relevant attributes or generate new attributes through the
22 preprocessing module. The partitioning module allows for more complex partitioning

1 schemes to be used with the spatial data in order to find more homogeneous data portions.
2 The prediction module assists the user in applying classification techniques and regression
3 techniques in order to predict real valued variables. The integration module improves
4 prediction methods through different integration and combining schemes provided by the
5 present invention. Finally, the recommendation module provides the user with
6 recommendations as to how to achieve a desired target value.

7 The spatial data analysis and modeling module is not limited to any particular set of
8 spatial data mining algorithms but is flexible to adapt to newly developed algorithms and
9 allows the user to create new prediction methods. The present invention allows for
10 algorithms created in a number of different programming environments to be useful in a
11 single system through unified control. Those skilled in the art will recognize that the present
12 invention is a valuable tool which enables a user to evaluate past and present data from
13 various sites in order to create history-based recommendations for that particular site.

14 Additional features and advantages of the invention will be set forth in the description
15 which follows, and in part will be obvious from the description, or may be learned by the
16 practice of the invention. The features and advantages of the invention may be realized and
17 obtained by means of the instruments and combinations particularly pointed out in the
18 appended claims. These and other features of the present invention will become more fully
19 apparent from the following description and appended claims, or may be learned by the
20 practice of the invention as set forth hereinafter.
21

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the manner in which the above-recited and other advantages and features of the invention are obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 illustrates an exemplary system that provides a suitable operating environment for the present invention;

Figure 2 illustrates a block diagram that represents an exemplary relationship among users and the spatial data analysis module of the present invention;

Figure 3 illustrates a block diagram that represents the interactions between various processes of the spatial data analysis module of Figure 2; and

Figure 4 illustrates a preferred embodiment of the present invention, wherein the data processing module is shown as a number of discrete functions.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to knowledge discovery in spatial data and more particularly to systems and methods for analyzing and extracting useful information from the spatial data. Analyzing and modeling spatial data in accordance uses the following modules: a data generation and manipulation module; a data inspection module; a data

1 preprocessing module; a data partitioning module; a modeling module; and a model
2 integration module. In some embodiments of the present invention, not all of the
3 modules are used to successfully analyze and model the spatial data.

4 The embodiments of the present invention may comprise a special purpose or
5 general purpose computer including various computer hardware, as discussed in greater
6 detail below. Embodiments within the scope of the present invention also include
7 computer-readable media for carrying or having computer-executable instructions or data
8 structures stored thereon. Such computer-readable media can be any available media
9 which can be accessed by a general purpose or special purpose computer. By way of
10 example, and not limitation, such computer-readable media can comprise RAM, ROM,
11 EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other
12 magnetic storage devices, or any other medium which can be used to carry or store
13 desired program code means in the form of computer-executable instructions or data
14 structures and which can be accessed by a general purpose or special purpose computer.
15 When information is transferred or provided over a network or another communications
16 connection (either hardwired, wireless, or a combination of hardwired or wireless) to a
17 computer, the computer properly views the connection as a computer-readable medium.
18 Thus, any such connection is properly termed a computer-readable medium.
19 Combinations of the above should also be included within the scope of computer-
20 readable media. Computer-executable instructions comprise, for example, instructions
21 and data which cause a general purpose computer, special purpose computer, or special
22 purpose processing device to perform a certain function or group of functions.

1 Figure 1 and the following discussion are intended to provide a brief, general
2 description of a suitable computing environment in which the invention may be
3 implemented. Although not required, the invention will be described in the general context
4 of computer-executable instructions, such as program modules, being executed by computers
5 in network environments. Generally, program modules include routines, programs, objects,
6 components, data structures, etc. that perform particular tasks or implement particular
7 abstract data types. Computer-executable instructions, associated data structures, and
8 program modules represent examples of the program code means for executing steps of the
9 methods disclosed herein. The particular sequence of such executable instructions or
10 associated data structures represent examples of corresponding acts for implementing the
11 functions described in such steps.

12 Those skilled in the art will appreciate that the invention may be practiced in network
13 computing environments with many types of computer system configurations, including
14 personal computers, hand-held devices, multi-processor systems, microprocessor-based or
15 programmable consumer electronics, network PCs, minicomputers, mainframe computers,
16 and the like. The invention may also be practiced in distributed computing environments
17 where tasks are performed by local and remote processing devices that are linked (either by
18 hardwired links, wireless links, or by a combination of hardwired or wireless links) through
19 a communications network. In a distributed computing environment, program modules may
20 be located in both local and remote memory storage devices.

21 With reference to Figure 1, an exemplary system for implementing the invention
22 includes a general purpose computing device in the form of a conventional computer 20,

1 including a processing unit 21, a system memory 22, and a system bus 23 that couples
2 various system components including the system memory 22 to the processing unit 21. The
3 system bus 23 may be any of several types of bus structures including a memory bus or
4 memory controller, a peripheral bus, and a local bus using any of a variety of bus
5 architectures. The system memory includes read only memory (ROM) 24 and random access
6 memory (RAM) 25. A basic input/output system (BIOS) 26, containing the basic routines
7 that help transfer information between elements within the computer 20, such as during start-
8 up, may be stored in ROM 24.

9 The computer 20 may also include a magnetic hard disk drive 27 for reading from
10 and writing to a magnetic hard disk 39, a magnetic disk drive 28 for reading from or writing
11 to a removable magnetic disk 29, and an optical disk drive 30 for reading from or writing to
12 removable optical disk 31 such as a CD-ROM or other optical media. The magnetic hard
13 disk drive 27, magnetic disk drive 28, and optical disk drive 30 are connected to the system
14 bus 23 by a hard disk drive interface 32, a magnetic disk drive-interface 33, and an optical
15 drive interface 34, respectively. The drives and their associated computer-readable media
16 provide nonvolatile storage of computer-executable instructions, data structures, program
17 modules and other data for the computer 20. Although the exemplary environment described
18 herein employs a magnetic hard disk 39, a removable magnetic disk 29 and a removable
19 optical disk 31, other types of computer readable media for storing data can be used,
20 including magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges,
21 RAMs, ROMs, and the like.

1 Program code means comprising one or more program modules may be stored on the
2 hard disk 39, magnetic disk 29, optical disk 31, ROM 24 or RAM 25, including an operating
3 system 35, one or more application programs 36, other program modules 37, and program
4 data 38. A user may enter commands and information into the computer 20 through
5 keyboard 40, pointing device 42, or other input devices (not shown), such as a microphone,
6 joy stick, game pad, satellite dish, scanner, or the like. These and other input devices are
7 often connected to the processing unit 21 through a serial port interface 46 coupled to system
8 bus 23. Alternatively, the input devices may be connected by other interfaces, such as a
9 parallel port, a game port or a universal serial bus (USB). A monitor 47 or another display
10 device is also connected to system bus 23 via an interface, such as video adapter 48. In
11 addition to the monitor, personal computers typically include other peripheral output devices
12 (not shown), such as speakers and printers.

13 The computer 20 may operate in a networked environment using logical connections
14 to one or more remote computers, such as remote computers 49a and 49b. Remote
15 computers 49a and 49b may each be another personal computer, a server, a router, a network
16 PC, a peer device or other common network node, and typically include many or all of the
17 elements described above relative to the computer 20, although only memory storage devices
18 50a and 50b and their associated application programs 36a and 36b have been illustrated in
19 Figure 1. The logical connections depicted in Figure 1 include a local area network (LAN)
20 51 and a wide area network (WAN) 52 that are presented here by way of example and not
21 limitation. Such networking environments are commonplace in office-wide or enterprise-
22 wide computer networks, intranets and the Internet.

1 When used in a LAN networking environment, the computer 20 is connected to the
2 local network 51 through a network interface or adapter 53. When used in a WAN
3 networking environment, the computer 20 may include a modem 54, a wireless link, or other
4 means for establishing communications over the wide area network 52, such as the Internet.
5 The modem 54, which may be internal or external, is connected to the system bus 23 via the
6 serial port interface 46. In a networked environment, program modules depicted relative to
7 the computer 20, or portions thereof, may be stored in the remote memory storage device.
8 It will be appreciated that the network connections shown are exemplary and other means
9 of establishing communications over wide area network 52 may be used.

10 Figure 2 provides an exemplary system 200 that implements one embodiment of the
11 present invention. A user interacts with a graphical user interface (GUI) 204. Often, user
12 access is limited by means known in the art, such as password protection, encryption, and
13 the like. The GUI 204 may be a local, LAN or Internet interface that will allow one or more
14 server systems to interact with one or more clients. Typically, the GUI 204 is allows a user
15 to have access to and interact with the specific features of the spatial data analysis and
16 modeling module (hereinafter "SDAM module") 206.

17 In fundamental terms, a user provides the SDAM module 206 with spatial data,
18 which is represented by a database 208. The user manipulates and analyzes the database 208
19 through the GUI 204. The present invention contemplates a distinctive GUI 204 and the
20 SDAM module 206 is adapted to the unique features and methodologies of spatial data
21 analysis. For example, the GUI 204 allows the user to easily select spatial data mining
22 algorithms and other functions that assist in evaluating spatial data. The SDAM module 206

1 includes sub-modules that are used to analyze the spatial data contained in the database 208
2 and extract useful information.

3 Figure 3 illustrates the SDAM module 206 of the system 200 in more detail. The
4 SDAM module 206 is preferably divided into a number of process modules. Figure 3 shows
5 one embodiment of the structure that SDAM module 206 may assume: data loading and
6 generation module 210, inspection module 212, preprocessing module 214, partitioning
7 module 216, prediction module 218, integration module 220, and recommendation module
8 222. It will be appreciated that not all process modules are required to implement the present
9 invention and that certain modules may be omitted. Although the SDAM module 206
10 includes numerous functions useful for non-spatial data, the present invention is intended
11 primarily for mining spatial data.

12 The data loading and generation module 210 is used to load spatial data from the
13 database 208. Loading data also refers to generating data from the spatial data contained in
14 the database 208 according to specified attributes of the database 208. An "attribute" is used
15 to mean a characteristic of the data, for example, crop yield, nitrogen content, phosphorous
16 content, and other soil chemistry, slope, topography, and/or water capacity. If, for example
17 the database 208 contains agricultural spatial data, the data loading and generation module
18 210 can generate an attribute with nitrogen-like statistics from a wheat field. A user can use
19 the data loading and generation module 210 to generate data sets of varying complexity and
20 size. In another embodiment, the data loading and generation module 210 provides a
21 spatial data simulator which generates data comparable to real-life spatial data sets. The
22 spatial data simulator enables a user to specify various attributes of crop yield and can

1 specify parameters for each attribute. Using those attributes based on specified parameters,
2 the user can, for example, simulate crop yield. The user may test a certain algorithm for
3 prediction accuracy on a known set of parameters and can instruct the data loading and
4 generation module 210 through the GUI 204 to construct a set of spatial data accordingly.
5 The user may also test the resolution of the sampling, the accuracy of sensors, and which
6 attributes have more influence on crop yield than others. The benefits of spatial data
7 simulator will be readily appreciated in that it also allows the user to test different methods
8 on a single data set to compare the accuracy of the methods rather than testing the methods
9 on different data sets which provides little basis for comparison. Thus, a user can evaluate
10 and experiment with the SDAM module 206 using data sets of desired complexity and size.

11 The data loading and generation module 210 also provides for basic data partitioning
12 as is sometimes desirable. Estimating data generating processes by neural networks
13 (hereinafter "NNs") and similar methods often requires partitioning available data into
14 training, validation and test subsets. The validation data are used to prevent over-training
15 and the testing data are used to provide a fair assessment of a model's prediction ability. The
16 present invention provides for different partitioning schemes depending on the complexity
17 of the prediction method being used. Generally, simple data sets require random
18 partitioning, while more complex prediction methods, such as NNs, may require different
19 partitioning schemes.

20 In a preferred embodiment, the data loading and generation module 210 provides a
21 data partitioning scheme based on spatial blocking of data (as compared to simple random
22 partitioning) for deriving training, validation, and test subsets. For spatial regression

1 experiments, preferably, the test subset should be spatially separated from the model-fitting
2 data employed by the learning algorithm. In the data-partitioning phase, the area containing
3 the data (a field in an agricultural example) should be split into two spatially disjoint sub-
4 areas (sub-fields) used for model fitting and testing.

5 An important part of NN design process is deciding when to stop training to avoid
6 overfitting. One preferred approach is to use part of the model-fitting data as a training set
7 for designing the model, and to use the rest as validation data for stopping the training
8 process. Training is halted when the mean squared error (MSE) for the validation data starts
9 to increase. For spatially correlated training and validation sets, minimizing the error on the
10 training subset would likely minimize the error on a randomly chosen validation subset,
11 since each sample in the validation subset would have samples in the training subset as its
12 spatial neighbors. Therefore, it could be expected that the training of a NN with a randomly
13 selected validation subset would continue to the point of gross overfitting resulting in
14 increased training time and lower generalization accuracy.

15 To address this problem, the data loading and generation module 210 provides a
16 procedure that increases the separation distance between the data points of the training and
17 validation subsets. The model-fitting portion of the field is partitioned into squares of size
18 $M \times M$, and half of these squares are randomly assigned for use in training and the rest for
19 validation. One way to assign squares to the training and validation subsets is to use a
20 regular checkerboard-like partitioning, assigning neighboring squares to different subsets.
21 A checkerboard-like assignment has desirable packing properties maximizing the distance
22 between the points in the two subsets for a given size of squares. The size M of each square

1 should be selected such that the squares are sufficiently large to minimize the influence of
2 spatial correlation between training and validation data, and still small enough to provide a
3 training set representative of the variability of the model-fitting part of the field. The
4 generation and manipulation of spatial data by the data loading and generation module 210
5 are examples of steps for loading spatial data.

6 The inspection module 212 primarily provides basic and spatial statistics on a
7 particular region and its attributes. Correlograms, which are useful tools for describing the
8 spatial variation of data, plot of the correlation coefficient as a function of the separation
9 distance between data points. Preferably, the present invention selects M to be within a
10 range where correlograms of all topographic features start to approach zero. This minimizes
11 the spatial dependence between training and validation samples, and allows the validation
12 set to better track NN generalization capabilities during the training process.

13 NNs fitted on the obtained spatial data partitions are going to be unstable for two
14 reasons. First, training of feed forward multilayer NNs, as powerful nonlinear models, is
15 very dependent on weight initialization. Second, it is influenced by the training set choice
16 with small changes in the training set often causing larger changes in the predictor.
17 Preferably, the integration module 220 (discussed more fully below) handles the instability
18 of the NN models through multiple model averaging. In the bagging technique, each
19 predictor is independently trained on N data points sampled with replacement from the N
20 original data points of the training set and the ensemble prediction is obtained by averaging
21 all individual predictors. Spatial bagging is provided, which consists of training a number
22 of NNs for different random assignments of squares into training and validation subsets

1 followed by averaging the predictions of all such NNs. This procedure allows combining
2 desirable properties of spatial partitioning and ensemble predictors into a more powerful
3 prediction method.

4 Generally, spatial data partitioning leads to significantly faster training and somewhat
5 improved prediction as compared to using the typical random partitioning of training and
6 validation data. Spatial data partitioning is more beneficial when used with more complex
7 models, since the danger of overfitting increases with the model complexity. Note that a
8 variety of means may be profitably employed to perform the functions enumerated herein,
9 of partitioning spatial data. The above-described process simply represents one example of
10 a method for performing these functions. It should be understood that this process is
11 presented solely by way of example and should not be construed as limiting the scope of the
12 present invention in any way.

13 After the spatial data are loaded, generated, and/or partitioned as desired, a user can
14 select available methods with which to manipulate the data according to a default sequence
15 suggested on the GUI 204 or in a user controlled sequence.

16 The inspection module 212 provides several methods for providing basic spatial and
17 non-spatial statistics on a region and its attributes. The basic statistical information may
18 include such first order parameters as mean and variation. Other standard measures that can
19 be produced are histograms, scatterplots between two attributes, and schedule plots. The
20 inspection module 212 also creates QQ plots for comparing sample distributions with a
21 normal distribution, as well as for comparing two sample distributions. The inspection
22 module 212 also determines the correlation coefficients between attributes which is

1 displayed in tabular form. Preferably, all implemented operations display results in the form
2 of charts, plots and tables through GUI 204.

3 The inspection module 212 also provides spatially statistical information such as the
4 plot of the region and the spatial auto-correlation between data points in attribute space
5 shown through 2-D and 3-D perspective figures as well as through different types of
6 variograms and correlograms. 3-D perspective plots including contour lines can be rotated,
7 panned and zoomed in order to observe all relevant surface characteristics of the region.

8 The variograms and correlograms are used to characterize the spatial relationship
9 between data points for specified attributes. In variograms, a measure of the dissimilarity
10 between data points for distance h apart is obtained. The inspection module 212 plots the
11 estimated variograms obtained from the experimental data, and then fits the theoretic
12 variograms to the estimated ones. The correlograms give the same information as the
13 variograms, except in correlograms, a measure of similarity between data points is
14 considered. A variety of means exist to provide basic statistical information. The above-
15 described examples represent only a few methods for performing these functions. It should
16 be understood that these examples are presented solely by way of example and should not
17 be construed as limiting the scope of the present invention in any way.

18 The preprocessing module 214 provides for various preprocessing steps that are often
19 necessary to prepare data for further modeling. Spatial data often contain large amounts of
20 data arranged in multiple layers. These data may contain errors and may not be collected at
21 a common set of coordinates. Thus, the preprocessing module 214 provides for steps such
22 as data cleaning and filtering, data interpolation, data normalization, data discretization,

1 generating new attributes, feature selection, and feature extraction. Figure 4 illustrates
2 functions implemented by the preprocessing module 214.

3 Data cleaning and filtering module 230 is sometimes necessary due to the high
4 possibility of measurement noise during collection of the spatial data. Data cleaning consists
5 of removing duplicate data points and value outliers, as well as spatial outliers. Data can also
6 be filtered or smoothed by applying a median filter with a window size specified by the user.
7 This provides missing values by averaging the points from the immediate vicinity.

8 In many real life spatial domain applications, the resolution (data points per area) will
9 vary among data layers and the data will not be collected at a common set of spatial
10 locations. Therefore, the data interpolation module 232 is necessary to apply an interpolation
11 procedure to the data to change data resolution and to compute values for a common set of
12 points. Interpolation techniques appropriate for spatial data, such as kriging and
13 interpolation using the minimum curvature method, are often preferable and are provided in
14 the present step in addition to the regular interpolation techniques such as inverse distance
15 interpolation, triangulation techniques, and splining.

16 A data normalization module 234 supports at least two normalization methods. Data
17 normalization 234 can transform the data to a normal distribution or it can scale the data to
18 a specified range selected by user 202. A data discretization module 236 is necessary in
19 some modeling techniques such as association rules, decision tree learning and all
20 classification problems. The data discretization module 236 typically includes different
21 attribute and target splitting criteria. For example, a user might discretize the data into high

1 crop yield versus low crop yield. A user can also generate new attributes by applying
2 supported unary and binary operators to a set of existing attributes.

3 In domains with a large number of attributes, the feature selection module 240 is
4 often beneficial by removing irrelevant attributes. Generally, the feature selection module
5 240 allows a user to select the most relevant attributes that influence the target value (e.g.,
6 yield). At least two types of feature selection are supported. First, the user can start with one
7 attribute and select additional attributes as desired. Second, the user, starting from a full set
8 of attributes, can remove attributes one by one with the feature selection module 240. Thus,
9 the user can ascertain which attributes are most relevant and have the greatest impact on
10 prediction results.

11 Several selection techniques are used such as Performance Feedback Forward
12 Selection and Backward Elimination based on linear regression mean square error (MSE)
13 minimization. Other selection techniques such as Branch and Bound are also supported.
14 Further, various criteria such as inter-class and probabilistic selection criteria are supported
15 using Euclidean and Mahalanobis distance, respectively. In addition to sequential backward
16 and forward search applied with both criteria, the branch and bound search can also be used
17 with Mahalanobis distance. To test feature stability, feature selection methods can be
18 applied to different data subsets, and the most stable features selected.

19 In contrast to the feature selection module 240 where a decision is target-based, a
20 feature extraction module 242 provides for variance-based dimensionality reduction. The
21 basic objective of the feature extraction module 242 is to reduce the number of attributes into

1 a few new attributes. For example, if the data set contains 40 original attributes, the feature
2 extraction module 240 extracts these 40 attributes into 4 or 5 new attributes.

3 The feature extraction module 242 typically employs both linear Principal
4 Components Analysis and non-linear dimensionality reduction using 4-layer feed forward
5 NNs. The targets used to train these NNs are the input vectors themselves, so that the
6 network is attempting to map each input vector onto itself. This can be viewed as two
7 successive functional mappings. The first mapping, defined by the first two layers, projects
8 the original d -dimensional data into a r -dimensional sub-space ($r < d$) defined by the
9 activations of the units in the second hidden layer with r neurons. Similarly, the last two
10 layers of the NN define an inverse functional mapping from the r -dimensional sub-space
11 back into the original d -dimensional space. The transformed data can be plotted in d -
12 dimensional space ($d = 2, 3$) and resulting plots can be rotated, panned and zoomed to better
13 view possible data groupings.

14 A variety of other preprocessing functions may be employed in the present invention.
15 The above-described examples represent only a few methods for preprocessing spatial data.
16 It should be understood that these examples are presented solely by way of example and
17 should not be construed as limiting the scope of the present invention in any way.

18 Referring now back to Figure 3, the partitioning module 216 allows users to split the
19 data set into more homogenous data segments, thus providing better modeling results. In a
20 majority of spatial data mining problems, there are subregions wherein data points have more
21 similar characteristics and more homogenous distributions than in comparison to data points
22 outside these regions. In order to find these regions, the partitioning module 216 supports

1 data partitioning according to attributes or a target value (i.e., driving variables). The
2 partitioning module 216 can also partition using a quad tree to split a spatial region along its
3 x and y dimensions into 4 subregions. The partitioning module 216 also supports k-means-
4 based and distribution-based clustering designed for spatial databases and the use of entropy
5 and information gain to partition attribute space by means of regression trees.

6 While global equations are adequate for problems considering a single or a few
7 driving variables, they may not be adequate for more complex problems. In, for example,
8 precision agriculture, the driving variables may be weed density, soil N content, and soil
9 depth. Levels of various driving variables almost always change throughout a field, and the
10 response to a given level of a driving variable can change within a field because of
11 interactions with other driving variables. In addition, there are differences in data
12 distributions and significant amounts of noise can exist.

13 For these more complex problems, the partitioning model 216 provides locally
14 adapted models. The process is based on the premise that, given a rich feature set,
15 partitioning a field into spatial regions having similar attributes (i.e., driving variables)
16 should result in regions of similar yield responses. First, the data from all fields are analyzed
17 in order to define spatial regions having similar characteristics. Then, regression models
18 were built to describe the relationship between attributes and yield on the training field
19 subset of identified spatial regions.

20 This process is described in more detail as follows: To eliminate irrelevant and
21 highly correlated features, the user may use the regression-based feature selection module
22 240 for continuous target values and classification-based feature selection 240 for discrete

1 target values as discussed above with reference to the preprocessing module 214. In contrast
2 to the feature selection module 240 where a decision is often target-based, variance-based
3 dimensionality reduction through the feature extraction module 242 can also be considered.

4 Using the features derived through the feature selection module 240 and feature
5 extraction module 242, a Density-Based System for Discovering Clusters in Large Spatial
6 Databases with Noise (hereinafter "DBSCAN") clustering method can be used to partition
7 fields into similar regions ignoring the spatial attributes (x and y coordinates) and the yield
8 value. The DBSCAN algorithm can be applied to merge training and testing field data.
9 These fields need not be adjacent because the x and y coordinates were ignored in the
10 clustering process. The DBSCAN algorithm relies on a density-based notion of clusters and
11 was designed to discover clusters of arbitrary shape efficiently. The key idea of a density-
12 based cluster is that for each point of a cluster its *Eps*-neighborhood for some given $Eps > 0$
13 has to contain at least a minimum number of points (*MinPts*). That is, the density in the *Eps*-
14 neighborhood of points has to exceed some threshold. Furthermore, the typical density of
15 points inside clusters is considerably higher than outside of clusters. DBSCAN uses a simple
16 but effective heuristic for determining the parameters *Eps* and *MinPts* of the smallest cluster
17 in the database. The user can change the *Eps* and *MinPts* parameters of DBSCAN method
18 to change the size of the resulting clusters.

19 Thus, the process results in P_i partitions. Ideally, P_i partitions should have equal area.
20 Since the resulting partitions P_i are constructed without considering spatial information, the
21 next step is to identify the largest contiguous clusters C_i inside the training part of partitions
22 P_i , and also the largest contiguous clusters T_i inside the test field part of partitions P_i . The

1 identification of C_i and T_i is performed by collecting all the neighboring (x, y) points
2 belonging to P_i . Note that there may be 2 or more such regions in the fields.

3 To further specialize prediction in each training cluster C_i , the user 202 can also
4 identify subsets L_i , A_i and H_i by assigning C_i data into three equal-size parts according to the
5 yield. Hence, the subset L_i corresponds to the lower 33% of the yield in C_i while subsets A_i
6 and H_i represent the average 33% and the highest 33% of the yield in cluster C_i . Thus, three
7 yield prediction models can be fitted to each cluster in a training portion of the merged yield.
8 For each point in the test set, its corresponding cluster is identified. Then, the nearest point
9 from the training set which belongs to the same cluster is found and the corresponding
10 regression model is applied.

11 Prediction models using prediction module 218 (described more fully below) can be
12 developed for the entire training field, each cluster in the training field, and each part, L_i , A_i ,
13 and H_i , of each cluster in the training field. Linear regression models and multilayer (2-
14 layered) feedforward NN (NN) regression models, with back-propagation learning can be
15 trained on each spatial part C_i , L_i , A_i and H_i and can be applied to the corresponding
16 neighborhood parts in the test field. For each of these models, the user can measure the
17 Mean Square Error (MSE) of yield prediction on identified test parts.

18 The prediction module 218 (described more fully below) can also order C_i , L_i , A_i , and
19 H_i with corresponding test field data (T_i) in the P_i according to their distance from the T_i , L_i ,
20 A_i and H_i center points determined by mean. This can be measured based on Euclidean or
21 Mahalanobis distance among the various subsets of attributes obtained through the
22 preprocessing steps. Due to possible feature instability, the user 202 can perform an

1 independent feature selection process for each cluster C_i and use region-specific features for
2 computing distance.

3 Instead of ordering the test field data, the user can use the weighted majority k-
4 Nearest neighbor algorithm with weights inversely proportional to the distances from the
5 center point. Other methods of ordering the test field data by distance measurement can be
6 used to determine the appropriate model, such as, Bhattacharaya, Hand and Henley.

7 Thus, given training and test fields, the partitioning module 216 defines more
8 homogenous spatial regions in both fields. The training and test fields are merged to identify
9 spatial regions on the training field that have similar characteristics in attribute space to
10 corresponding spatial regions in the test field. Next, the partitioning module 216 builds local
11 regression models on spatial regions inside the training field, describing the relationship
12 between field characteristics and yield. Using these models, locally on corresponding spatial
13 test field regions provides better prediction on identified regions than using global prediction
14 models. Data partitioning using clustering in this manner can be followed by similarity-
15 based competency ordering using the prediction module 218, which is used to identify the
16 appropriate local regression model when making predictions for unseen fields. Generally,
17 this method of building local site-specific regression models outperforms global models.

18 The present invention contemplates another partitioning scheme through partitioning
19 module 216. This advanced data partitioning approach is based on the premise that fields
20 are heterogenous and that multiple, locally specialized models may be better suited for site-
21 specific yield prediction than a single global model. The partitioning module 216 provides
22 a sequence of local regressors each having a good fit on a particular training data subset,

1 constructing distribution models for identified subsets, and using these to decide which
2 regressor is most appropriate for each test datapoint.

3 Partitioning module 216 also provides an iterative data partitioning scheme based on
4 an analysis of spatially filtered errors of multiple local regressors and the use of statistical
5 tests for determining if further partitioning is needed for achieving homogenous regions.

6 A variety of methods have been developed to partition data. The above-described
7 examples represent only a few methods for performing this function. It should be
8 understood that these examples are presented solely by way of example and should not be
9 construed as limiting the scope of the present invention in any way.

10 Prediction module 218 is used to build models that describe relationships between
11 attributes and target values. Generally, the prediction module 218 is used in conjunction
12 with the previous features described above and has been mentioned in some of the previous
13 features, for example, with respect to partitioning module 216, to show that the prediction
14 modeling steps naturally follow some of the preprocessing steps.

15 For novice users, an automatic configuration of the parameters used in the spatial data
16 mining algorithms is supported. When a novice user interacts with the GUI 204 in order to
17 model the data, the most appropriate parameters are suggested to the user through the GUI
18 204, according to the data sets and the selected model. More experienced data mining
19 experts may change the proposed configuration parameters through the GUI 204 and
20 experiment with miscellaneous algorithm settings.

21 The user can select from multiple classification and regression procedures through
22 the GUI 204. Modeling functions are divided into classification and regression algorithms.

1 In classification, the user 202 is concerned with predicting the class into which data should
2 fall. For example, if user 202 has discretized the data into low, average, and high yield, the
3 classification model tries to classify the data into these three classes. For regression, the user
4 202 is trying to predict the target value. For example, in precision agriculture, the target
5 value is the crop yield.

6 The prediction module 218 provides for classification procedures using algorithms
7 based on association rules, k-Nearest Neighbor, NNs, and the like. Linear regression
8 procedures utilize algorithms based on linear regression models, CART regression trees,
9 weighted k-Nearest Neighbor, NNs, and the like. One skilled in the art will recognize that
10 classification and linear regression models are not limited to the algorithms described above
11 and that the algorithms described above are examples of the types of algorithms and not
12 meant to be limiting in any way.

13 The user can also apply tested models on a totally unseen new data set. All
14 prediction results are graphically displayed on the GUI 204. The GUI 204 can also display
15 the results of the NN (NN) learning process, including the learned structures of NNs and
16 regression trees.

17 Given different prediction models, several methods for improving their prediction
18 accuracy are implemented through different integration and combining schemes provided by
19 the integration module 220. In machine learning theory, combining multiple classifiers is
20 an effective technique for improving prediction accuracy. There are many general
21 combining algorithms such as bagging, boosting, or Error Correcting Output Codes (ECOC)
22 that significantly improve global classifiers like decision trees, rule learners, and NNs.

1 An ensemble of classifiers must be both diverse and accurate in order to improve
2 accuracy of the whole. Diversity is required to ensure that all the classifiers do not make the
3 same errors. In order to increase the diversity of combined classifiers for spatial
4 heterogeneous databases with attribute instability, one cannot assume that the same set of
5 attributes is appropriate for each single classifier. For each training sample, drawn in a
6 bagging or boosting iteration, a different set of attributes is relevant and therefore each single
7 classifier in iteration should use the appropriate attribute set. In addition, the application of
8 different classifiers on spatial databases, where the data are highly spatially correlated, may
9 produce spatially correlated errors. In such situations the standard combining methods might
10 require different schemes for manipulating the training instances in order to keep the
11 diversity of classifiers.

12 The integration module 220 provides that the boosting algorithm is modified in order
13 to successfully deal with unstable driving attributes which are common in spatial domains.
14 The integration module 220 provides a modification of the AdaBoost algorithm for
15 combining multiple classifiers to improve overall classification accuracy. In each boosting
16 round the present invention maximizes the local information for a drawn sample by changing
17 attribute representation through attribute selection, attribute extraction and appropriate
18 attribute weighting methods. In order to exploit the spatial data knowledge, a modification
19 of the boosting method appropriate for heterogeneous spatial databases is provided, where
20 at each boosting round spatial data blocks are drawn instead of the standard approach of
21 sampling single instances.

The influence of these adjustments to single classifiers is not the same for local classifiers (e.g., k-nearest neighbor) and global classifiers (e.g., artificial NNs). Standard combining methods do not improve simple local classifiers due to correlated predictions across the outputs from multiple combined classifiers. Prediction of combined nearest neighbor classifiers can be decorrelated by selecting different attribute representations for each sample and by sampling spatial data blocks. The nearest neighbor classifier is often criticized for slow run-time performance and large memory requirements, and using multiple nearest neighbor classifiers could further worsen the problem. Therefore, the present invention provides a method for k-nearest neighbor classification to speed up the boosting process.

The modified AdaBoost algorithm is described as follows:

1. Given : Set $S \{(x_1, y_1), \dots, (x_m, y_m)\}$ $x_i \in X$, with labels $y_i \in Y = \{1, \dots, k\}$
2. Initialize the distribution D_1 over the examples, such that $D_1(i) = 1/m$
3. For $t = 1, 2, 3, 4, \dots T$

Find relevant feature information for distribution D_t

1. Train weak learner using distribution D_t
2. Compute weak hypothesis $h_t: X \rightarrow Y \rightarrow [0,1]$
3. Compute the pseudo-loss of hypothesis h_t :

$$\varepsilon_t = \frac{1}{2} \cdot \sum_{(i,y) \in B} D_t(i,y) (1 - h_t(x_i, y_i) + h(x_i, y))$$

4. Set $\beta_t = \varepsilon_t / (1 - \varepsilon_t)$

5. Update D_t : $D_{t+1}(i,y) = (D_t(i,y) / Z_t) \cdot \beta_t^{(1/2) \cdot (1 - h_t(x_i, y_i) + h(x_i, y_i))}$

Where Z_t is a normalization constant chosen such that D_{t+1} is a distribution

4. Output the final hypothesis: $h_{fn} = \arg \max_{y \in Y} \sum_{t=1}^T (\log \frac{1}{\beta_t}) \cdot h_t(x, y)$

1 The modified algorithm maintains a distribution D_t over the training examples,
2 which can be initially uniform. The algorithm proceeds in a series of T rounds. In each
3 hypothesis h_t . The distribution is updated to give wrong classifications higher weights than
4 correct classifications.

5 Since each boosting iteration t will have different training samples drawn according
6 to the distribution D_t , at the beginning of the "for loop" described above, the present
7 invention modifies the standard algorithm by adding step 0., wherein, a different attribute
8 representation for each sample is chosen. Different attribute representations are realized
9 through attribute selection, attribute extraction and attribute weighting processes through
10 boosting iterations. This forces individual classifiers to make different and uncorrelated
11 errors.

12 Error correlation is related to Breiman's concept of stability in classifiers. Nearest
13 neighbor classifiers are stable to the patterns, so bagging and boosting generate poor k-NN
14 ensembles. Nearest neighbor classifiers, however, are extremely sensitive to the attributes
15 used. This process attempts to use this instability to generate a diverse set of local
16 classifiers with uncorrelated errors. At each boosting round, one of the following methods
17 is performed to determine a suitable attribute space for each use in classification.

18 To eliminate irrelevant and highly correlated attributes, regression-based attribute
19 selection is performed through performance feedback forward selection and backward
20 elimination search techniques based on linear regression mean square error (MSE)
21 minimization. The r most relevant attributes are selected according to the selection criterion
22 at each round of boosting, and are used by the k-NN classifiers.

1 In contrast to attribute selection where a decision is target-based, variance-based
2 dimensionality reduction through attribute extraction is also considered. Here, linear
3 Principal Components Analysis (PCA) can be employed. Each of the k-NN classifiers uses
4 the same number of new transformed attributes. Another possibility is to choose an
5 appropriate number of newly transformed attributes which will retain some predefined part
6 of the variance.

7 The attribute weighting method used in the provided method is based on a 1-layer
8 feedforward NN. First, integration module 220 performs target value prediction for the
9 drawn sample with defined a 1-layer feedforward NN using all attributes. This kind of NN
10 can discriminate relevant from irrelevant attributes. Therefore, the NNs interconnection
11 weights are taken as attribute weights for the k-NN classifiers.

12 To further test attribute stability properties, miscellaneous attribute selection
13 algorithms can be applied on the entire training set and the most stable attributes selected.
14 Then the standard boosting method can be applied to the k-NN classifiers using the
15 identified fixed set of attributes at each boosting iteration. When boosting is applied with
16 attribute selection at each boosting round, the attribute occurrence frequency is monitored
17 in order to compare the most stable selected attributes. When attribute subsets selected
18 through boosting iterations become stable, this can be an indication to stop the boosting
19 process.

20 The modified algorithm for combining multiple classifiers can result in significantly
21 better predictions over existing classifier ensembles, especially for heterogeneous data sets
22 with attribute instabilities. By manipulating the attribute representation used by individual

1 classifiers at each boosting round, the classifiers can be more decorrelated, thus leading to
2 higher prediction accuracy. The attribute stability test serves as a good indicator for proper
3 stopping of further boosting iterations. Generally, a small number of iterations is needed
4 in order to achieve the same final prediction accuracy.

5 The present invention also contemplates methods for spatial boosting of k-NN
6 classifiers, adaptive attribute and spatial boosting for NN classifiers, and a fast k-NN
7 algorithm. A variety of methods have been developed to combine and integrate prediction
8 models. The above-described examples represent only a few methods for performing this
9 function. It should be understood that these examples are presented solely by way of
10 example and should not be construed as limiting the scope of the present invention in any
11 way.

12 The recommendation module 222 provides user 202 with recommendations as to
13 how to achieve a specific target value. For example, in precision agriculture, the user is
14 interested in obtaining the best crop yield (the target value). Thus, the user must know how
15 much fertilizer (i.e., nitrogen, phosphorous, etc.) to apply on each point of the field based
16 on the results of the data analysis. The recommendation module 222 takes the results of the
17 spatial data analysis and provides a map of the field and indicates how much fertilizer
18 should be applied to each point on the field.

19 The recommendation module 222 may provide different types of information. For
20 example, the recommendation module 222 could be converted into a fertilizer module,
21 meaning that the parameter that is evaluated is how much fertilizer should be applied to
22 each point based on the spatial data analysis. Or the recommendation module could be

1 converted into an irrigation module which would evaluate how much to irrigate the field at
2 predetermined points. Other examples include pesticide module, herbicide module, seed-
3 variety spacing module, and the like.

4 One example of how the recommendation module could be implemented is
5 described in U.S. Provisional application S/N 60/077,583, filed on March 10, 1998,
6 incorporated herein by reference. The recommendation module can be used to create
7 "recipes" for optimizing the treatment of spatial environments. The results of the spatial
8 data analysis provided by the present invention can be used to create optimal recipes for
9 various treatments which include, but are not limited to, a fertilizer schedule, an irrigation
10 schedule, a herbicide schedule, a pesticide schedule, a seed-variety spacing schedule, an
11 agricultural equipment schedule, and the like.

12 The present invention provides for prediction of values of a specific field by
13 interpolating from various tested point or block sampling. A recipe for optimizing, for
14 example, nitrogen levels would occur through the following steps. The analysis begins by
15 obtaining a fact from the spatial database. A preliminary determination about the obtained
16 fact is made against the backdrop of the current statements to see if the fact can or cannot
17 be executed. If the fact cannot be executed, the fact is discarded. An example of non-
18 compliance and discarding is as follows: if the fact states "keep nitrogen below 42 ppm for
19 wheat production" and a current statement indicates that the soil at a particular site in a field
20 for growing wheat is determined to be 46 ppm nitrogen, the fact cannot be executed; the fact
21 is then discarded. Discarding of the facts in this manner eliminates superfluous data from
22 being considered when the recipe is being devised. Thus the final recipe is free from

1 extraneous data. Once discarded, the method then ascertains whether other facts are
2 available. If so, the steps are iteratively processed until all facts have been examined.

3 If the fact can be executed, then the method isolates facts that can be executed and
4 groups these facts together as "stored facts." Stored facts are merely a means for describing
5 the computer-executable instructions for isolating and/or maintaining facts until such time
6 as they are further considered as part of the recipe.

7 After ascertaining the first fact, the method then proceeds to evaluate another fact,
8 for example, economic considerations to determine if the stored facts also meet economic
9 criteria. Once all the facts are evaluated, the method has provided a recipe whereby the
10 agriculturalist is enabled to most economically fertilize the agricultural field.

11 Another advantage of the recommendation module 222 is that it provides results
12 which can be utilized in systems that monitor agricultural machinery and make real time
13 adjustments to the agricultural machinery such that the operation of the machinery is
14 optimized. The optimization can be related to the crop yield or other quality standards or
15 group of standards. The optimization of the agricultural machinery is performed by
16 analyzing data through the systems and methods of the present invention and then relaying
17 that information directly or wirelessly to agricultural machinery equipped to modify output
18 of measurements. The results from the present invention in conjunction with the
19 autonomous control of agricultural machinery provide for optimum yields, with minimum
20 human effort. For example, once the recommendation module 222 has completed analyzing
21 a set of agricultural data, the recommendations can be relayed to agricultural equipment

1 which will automatically modify the output of fertilizer depending on the specific
2 geographic point, thus optimizing the crop yield.

3 Thus, the SDAM module 206 provides various systems and methods allow a user
4 to effectively predict and analyze spatial data. The present invention provides for virtually
5 all existing algorithms presently being used in the area of spatial data mining to be
6 implemented in the methods and systems described because new algorithms can be added
7 to the SDAM module 206. One skilled in the art will appreciate that the SDAM module
8 206 is provided with remarkable flexibility to assist a user in an interactive knowledge
9 discovery process. The SDAM module 206 in essence supports the whole knowledge
10 discovery process.

11 One skilled in the art will recognize that the systems and methods of the present
12 invention can be readily applied to spatial data in precision agriculture. Agricultural
13 producers are collecting large amounts of spatial data using global positioning systems to
14 georeference sensor readings and sampling locations. Based on the interpretation of spatial
15 data sets that include features such as topography, soil type, soil fertility levels, remotely
16 sensed crop yields, management decisions can be varied instead of keeping them constant
17 across an entire field area. The systems and methods of the present invention offer the
18 potential to develop site-specific regression functions from spatial agricultural data that,
19 given the ability to predict yield response, would allow calculation of optimum levels of
20 production inputs.

21 One advantage that can be readily appreciated is that the present invention provides
22 researchers with the ability to use the knowledge obtained from one data set and extrapolate

1 this knowledge to different agricultural sites, or to the same site, but different years. This
2 is possible because one objective of the present invention is to explain yield variability as
3 a function of the site-specific driving variable. In other words, the present invention
4 provides the ability to analyze how different attributes affect the target value. This objective
5 differs from the majority of research encountered in geostatistics or spatial econometrics
6 where the goal is limited to spatial interpolation, that is, simply obtaining the target value.
7 This ability is a valuable tool that will lead to more efficient and productive management.

8 The SDAM module 206 described above contains the flexibility to provide a number
9 of different algorithms in a number of different programming environments. The present
10 invention provides for a unified GUI 204 which is compatible with more than one
11 programming environment. The SDAM module 206 also contains the flexibility to add
12 more algorithms to its files as more algorithms are developed.

13 The present invention may be embodied in other specific forms without departing
14 from its spirit or essential characteristics. The described embodiments are to be considered
15 in all respects only as illustrative and not restrictive. The scope of the invention is,
16 therefore, indicated by the appended claims rather than by the foregoing description. All
17 changes which come within the meaning and range of equivalency of the claims are to be
18 embraced within their scope.